

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : O/P-Toluene Sulfonamide CAS-No. : 1333-07-9 or 8013-74-9

Synonym: O/P-Toluene sulphonamide; O/P-Toluenesulfonamide;

O/PTSA; Ortho Para Toluene Sulfonamide; Toluenesulfonamide

Company: Jiaxing Kingvolt Import & Export Co.,Ltd

Address: 2002, A Building, Yaocheng Plaza, No.1520, East Zhongshan RD

Jiaxing City, Zhejiang Province, 314000 China,.

Telephone: +86-573-82118911

Fax: +86-573-8118912

Emergency Phone #: +86-15157335533

E-mail: sales@kingvolt.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Formula: C₇H₉NO₂S

CAS-No. EC-No. Index-No. Concentration

O/P-Toluene Sulfonamide

 1333-07-9
 215-578-1
 >99%

 8013-74-9
 232-394-7
 >99%

CAS-No. Chemical Name Content 70-55-3 P-Toluenesulfonamide 60-90% 88-19-3 Ortho-Toluenesulfonamide 40-10%

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Not available.

Potential Health Effects

The toxicological properties of this material have not been investigated. Use appropriate procedures to prevent opportunities for direct contact with the skin or eyes and to prevent inhalation.

4. FIRST AID MEASURES

Eyes:

Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids.

Skin:

Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes.

Ingestion:

Do NOT induce vomiting. If conscious and alert, rinse mouth and drink 2-4 cupfuls of milk or water.

Inhalation:

Remove from exposure to fresh air immediately.

Notes to Physician:

5. FIRE-FIGHTING MEASURES

General Information:

As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Extinguishing Media:

In case of fire, use water, dry chemical, chemical foam, or alcohol-resistant foam.

6. ACCIDENTAL RELEASE MEASURES

General Information:

Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks:

Clean up spills immediately, observing precautions in the Protective Equipment section. Sweep up, then place into a suitable container for disposal.

7. HANDLING AND STORAGE

Handling:

Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Avoid contact with eyes, skin, and clothing. Avoid ingestion and inhalation.

Storage:

Store in a cool, dry place. Keep container closed when not in use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Use process enclosure, local exhaust ventilation, or other engineering controls to control airborne levels.

Personal Protective Equipment

Eves:

Wear safety glasses and chemical goggles if splashing is possible.

Skin:

Wear appropriate protective gloves and clothing to prevent skin exposure.

Clothing:

Wear appropriate protective clothing to minimize contact with skin.

Respirators:

Wear a NIOSH/MSHA or European Standard EN 149 approved full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Crystalline powder

Appearance: white

Odor: Not available.

pH: Not available.

Vapor Pressure: Not available.

Viscosity: Not available.

Boiling Point: 221°C @ 10.00mmHg

Freezing/Melting Point: 102.00 - 130.00°C

Autoignition Temperature: Not available. **Flash Point:** 202°C (395.60°F)

Explosion Limits, lower:Not available. **Explosion Limits, upper:**Not available.

Decomposition Temperature:

Solubility in water: $0.28 \text{ g/100ml } (25 \,^{\circ}\text{C})$

Specific Gravity/Density:

Molecular Formula: $C_7H_9NO_2S$ Molecular Weight: 171.21

10. STABILITY AND REACTIVITY

Chemical Stability:

Stable under normal temperatures and pressures.

Conditions to Avoid:

Incompatible materials, strong oxidants.

Incompatibilities with Other Materials:

Strong oxidizing agents, strong bases.

Hazardous Decomposition Products:

Nitrogen oxides, carbon monoxide, oxides of sulfur, irritating and toxic fumes and gases, carbon dioxide, nitrogen.

Hazardous Polymerization:

Has not been reported.

11. TOXICOLOGICAL INFORMATION

RTECS#:

CAS# 88-19-7;70-55-3: XT5075000

LD50/LC50:

Not available.

Carcinogenicity:

O/ P-TOLUENESULFONAMIDE

Not listed by ACGIH, IARC, NIOSH, NTP, or OSHA.

See actual entry in RTECS for complete information.

12. ECOLOGICAL INFORMATION

None known.

13. DISPOSAL CONSIDERATIONS

Dispose of in a manner consistent with federal, state, and local regulations.

14. TRANSPORT INFORMATION

IATA

Not regulated as a hazardous material.

IMO

Not regulated as a hazardous material.

RID/ADR

Not regulated as a hazardous material.

15. REGULATORY INFORMATION

European/International Regulations

European Labeling in Accordance with EC Directives

Hazard Symbols:

Not available.

Risk Phrases:

Safety Phrases:

S 24/25 Avoid contact with skin and eyes.

WGK (Water Danger/Protection)

CAS# 88-19-7;70-55-3: 1

United Kingdom Occupational Exposure Limits

Canada

CAS# 88-19-7;70-55-3 is listed on Canada's DSL List.

CAS# 88-19-7;70-55-3 is not listed on Canada's Ingredient Disclosure List.

Exposure Limits

US FEDERAL

TSCA

CAS# 88-19-7;70-55-3 is listed on the TSCA inventory.

16. OTHER INFORMATION

Further information

Copyright 2013 Jiaxing Kingvolt Import & Export Co.Ltd License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Jiaxing Kingvolt Import & Export Co.Ltd shall not be held liable for any damage resulting from handling or from contact with the above product.